Printing date: 05.03.2020 Version: 8 Revision: 05.03.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: CONTACT / ELECTRO CLEANER (Oil containing)
- · Article number: 18-00000-1076
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture Surface cleaning
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:
- · Further information obtainable from:
- 1.4 Emergency telephone number:

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319

Causes serious eye irritation.

STOT SE 3 H336

May cause drowsiness or dizziness.

Asp. Tox. 1 H304

May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

propan-2-ol

Hydrocarbons, C10-C13, n-alkanes, cyclic, <2% aromates, Benzene <0.1%

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101

If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

Printing date: 05.03.2020 Version: 8 Revision: 05.03.2020

Trade name: CONTACT / ELECTRO CLEANER (Oil containing)

30000		(Contd. of page 1)
	P102	Keep out of reach of children.
		Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Do not pierce or burn, even after use.
	P261	Avoid breathing spray.
	P271	Use only outdoors or in a well-ventilated area.
	P280	Wear protective gloves / eye protection.
	P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
		present and easy to do. Continue rinsing.
	P403	Store in a well-ventilated place.
	P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
	P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
	· Additional inform	
		The state of the s

Buildup of explosive mixtures possible without sufficient ventilation.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Active substance with propellant

Dangerous components:		105 -500/
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<25%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons,C10-C13,n-alkanes,cyclic,<2%aromates, Benzene <0.1% Asp. Tox. 1, H304	10-<25%
CAS: 8042-47-5 EINECS: 232-455-8 Reg.nr.: 01-2119487078-27	White mineral oil, petroleum substance with a Community workplace exposure limit	2.5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-<10%
CAS: 119-36-8 EINECS: 204-317-7 Reg.nr.: 01-2119515671-44	methyl salicylate Acute Tox. 4, H302; Eye Irrit. 2, H319	1-<2.5%

## Ingredients according to detergents guidline 648/2004/EC aliphatic hydrocarbons

Additional information:

≥30%

Printing date: 05.03.2020 Version: 8 Revision: 05.03.2020

Trade name: CONTACT / ELECTRO CLEANER (Oil containing)

(Contd. of page 2)

#### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

### **SECTION 6: Accidental release measures**

### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

(Contd. on page 4)

Printing date: 05.03.2020 Version: 8 Revision: 05.03.2020

Trade name: CONTACT / ELECTRO CLEANER (Oil containing)

(Contd. of page 3)

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· 8.1 Control parameters	
Ingredients with limit values that require monitoring at the workplace:	7.55
Hydrocarbons,C10-C13,n-alkanes,cyclic,<2%aromates, Benzene <0.1%	
TLV Short-term value: 1200, 184	
8042-47-5 White mineral oil, petroleum	
TLV   Short-term value: 5 mg/m <sup>3</sup>	

	TGG, 8-urige werkdag	
· DNE	Ls	

(	67-63-0 propan-2-ol				
(	Oral	DNEL Long term-systemic	26 mg/kg bw/day (Consumer)		
I	Dermal	DNEL Long term-systemic	319 mg/kg bw/day (Consumer)		
			888 mg/kg bw/day (Worker)		
]	Inhalative	DNEL Long term-systemic	89 mg/m3 (Consumer)		
			500 mg/m3 (Worker)		
	119-36-8 r	nethyl salicylate			
(	Oral	DNEL Acute-systemic	5 mg/kg bw/day (Consumer)		
		DNEL Long term-systemic	1 mg/kg bw/day (Consumer)		
]	Dermal	DNEL Long term-systemic	3 mg/kg bw/day (Consumer)		
			6 mg/kg bw/day (Worker)		
1	Inhalative	DNEL Acute-systemic	213 mg/m3 (Consumer)		
			285 mg/m3 (Worker)		
		DNEL Long term-systemic	4 mg/m3 (Consumer)		

	17.5 mg/m3 (Worker)
· PNECs	
119-36-8 methyl salicylate	
PNEC Freshwater	0.0016 mg/l (Undefind)
PNEC Marine water	0.00016 mg/l (Undefind)
PNEC Freshwater sediment	0.0412 mg/l(dry weight) (Undefind)
PNEC Soil	0.35 ug/kg (Undefind)
PNEC Sewage Treatment Plan	140 mg/l (Undefind)
PNEC Marine water sediment	0.0412 mg/l(dry weight) (Undefind)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 5)

Revision: 05.03.2020 Printing date: 05.03.2020 Version: 8

Trade name: CONTACT / ELECTRO CLEANER (Oil containing)

(Contd. of page 4)

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2/P2

#### Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Wear gloves for the protection against chemicals according to EN 374

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

#### Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### Eye protection:

Safety glasses



Tightly sealed goggles

· Body protection: Use protective suit. (EN-13034/6)

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:

Colour:

· Odour:

According to product specification

Characteristic

· Odour threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition

Melting point/freezing point: Initial boiling point and boiling range: -44.5 °C

Undetermined.

· Flash point:

-97 °C

· Flammability (solid, gas):

Not applicable.

(Contd. on page 6)

Printing date: 05.03.2020 Version: 8 Revision: 05.03.2020

Trade name: CONTACT / ELECTRO CLEANER (Oil containing)

	(Contd. of page
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	12 Vol %
· Vapour pressure at 20 °C:	8300 hPa
Density at 20 °C:	0.682 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	7.500 - 10.500 Brookfield sp3 6 rpm
	4.000 - 6000 Brookfield sp3 12 rpm
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	90.9 %

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

67-63-0 p	ropan-2-ol		
Oral	LD50	5840 mg/kg (Rat)	
Dermal	LD50	13900 mg/kg (Rabbit)	
Inhalative	LC50 (6h)	25000 mg/m3 (Rat)	
Hydrocar	bons,C10-0	C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%	
Oral	LD50	>5000 mg/kg (Rat)	
Dermal	LD50	>5000 mg/kg (Rabbit)	
Inhalative	LC50/4 h	4951 mg/l (Rat)	
119-36-8	methyl salid	cylate	
Oral	LD50	5000 mg/kg (Rabbit)	

Printing date: 05.03.2020 Version: 8 Revision: 05.03.2020

Trade name: CONTACT / ELECTRO CLEANER (Oil containing)

(Contd. of page 6)

887 mg/kg (Rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

#### **SECTION 12: Ecological information**

· 12.1 Toxicity

Aquatic toxicity:				
67-63-0 propan-2-ol				
LOEC (8 days)	1000 mg/l (Algae)			
LC50 (96h)	9640 mg/l (Pimephales promelas)			
LC50 (24h)	9714 mg/l (Daphnia magna)			
Hydrocarbons,	C10-C13,n-alkanes,cyclic,<2%aromates, Benzene <0.1%			
EL0 (48h)	1000 mg/l (Daphnia magna)			
EL0 (72h)	1000 mg/l (Pseudokirchneriella subcapitata)			
LL0 (96h)	1000 mg/l (Onc)			

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

·Euro	pean waste catalogue	
HP3	Flammable	
HP4	Irritant - skin irritation and eye damage	
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	(C 11 2)

(Contd. on page 8)

Version: 8 Revision: 05.03.2020 Printing date: 05.03.2020

Trade name: CONTACT / ELECTRO CLEANER (Oil containing)

(Contd. of page 7)

· Uncleaned packaging:
· Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, ADN, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR, ADN · IMDG · IATA	UN1950 AEROSOLS AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
· Class · Label	2 5F Gases. 2.1
· ADN · ADN/R Class:	2 5F
IMDG, IATA	
· Class · Label	2.1 2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code):	Warning: Gases.
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity abov 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2 For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2

Revision: 05.03.2020 Version: 8 Printing date: 05.03.2020

Trade name: CONTACT / ELECTRO CLEANER (Oil containing)

	(Contd. o	of page 8
· Transport/Additional information:		
· ADR · Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity	
· Tunnel restriction code	D	
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity	
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1	

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:

Class	Share in %
NK	75-<100

- · VOC-CH 90.90 %
- · VOC-EU 619.9 g/l
- · Danish MAL Code 4-3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Department issuing SDS:

Produktsicherheit

Research & Development

- · Contact: Ing. J. Sleumer
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

(Contd. on page 10)

Page 10/10

## Safety data sheet according to 1907/2006/EC, Article 31

Revision: 05.03.2020 Version: 8 Printing date: 05.03.2020

Trade name: CONTACT / ELECTRO CLEANER (Oil containing)

(Contd. of page 9)

Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 4: Acute toxicity - oral – Category 4
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1