

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**WINKEL WW3000 Haftschiemier Spray 500ml**

Revision date: 13.07.2020

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

WINKEL WW3000 Haftschiemier Spray 500ml

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Lubricants, greases, release products

**1.3. Details of the supplier of the safety data sheet**

Company name: WINKEL GmbH  
Street: Lisztstrasse 1  
Place: 53881 Euskirchen - Germany  
Telephone: +49 2251 77 69 400-401  
e-mail: info@winkelgroup.de  
Internet: www.winkelgroup.de

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard components for labelling**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt; 5% n-hexane

Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics

**Signal word:** Danger**Pictograms:****Hazard statements**

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## WINKEL WW3000 Haftschmier Spray 500ml

Revision date: 13.07.2020

Page 2 of 13

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves and eye/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**2.3. Other hazards**

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.  
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
75-28-5	isobutane			50 - <= 100 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
74-98-6	propane			5 - < 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			3 - < 5 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics			3 - < 5 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
4259-15-8	zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)			0.1 - < 1 %
	224-235-5		01-2119493635-27	
	Eye Dam. 1, Aquatic Chronic 2; H318 H411			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**WINKEL WW3000 Haftschmier Spray 500ml**

Revision date: 13.07.2020

Page 3 of 13

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

**After inhalation**

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with skin**

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with eyes**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

**4.2. Most important symptoms and effects, both acute and delayed**

Headache, nausea, dizziness, fatigue, skin irritation

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder.

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

**5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Danger of bursting container.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Wear personal protection equipment.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**WINKEL WW3000 Haftschmier Spray 500ml**

Revision date: 13.07.2020

Page 4 of 13

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Observe instructions for use.  
Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.  
When using do not eat, drink, smoke, sniff.  
Wear personal protection equipment (refer to section 8).  
In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

**Further information on handling**

Avoid contact with skin and eyes.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Observe legal regulations and provisions.

**Hints on joint storage**

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

**Further information on storage conditions**

Protect from frost. Protect against direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

**7.3. Specific end use(s)**

No information available.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## WINKEL WW3000 Haftschmier Spray 500ml

Revision date: 13.07.2020

Page 5 of 13

## DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
64742-49-0	Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics			
Worker DNEL, long-term		inhalation	systemic	2085 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	300 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	447 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	149 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	149 mg/kg bw/day

## Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long term exposure: after several previous shifts
- d before next shift

blood (B)

Urine (U)

**8.2. Exposure controls****Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Protective and hygiene measures**

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

**Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.

DIN EN 166

**Hand protection**

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min

Thickness of the glove material 0,45 mm

EN ISO 374

**Skin protection**

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

**Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## WINKEL WW3000 Haftschmier Spray 500ml

Revision date: 13.07.2020

Page 6 of 13

**Environmental exposure controls**

Observe legal regulations and provisions.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state: Aerosol  
Colour: brown  
Odour: characteristic

**Test method**

pH-Value (at 20 °C): not determined DIN 19268

**Changes in the physical state**

Melting point: not determined  
Initial boiling point and boiling range: -40 °C  
Sublimation point: No information available.  
Softening point: No information available.  
Flash point: -80 °C

**Flammability**

Solid: not applicable  
Gas: not applicable

Lower explosion limits: 1,5 vol. %  
Upper explosion limits: 15 vol. %  
Ignition temperature: No information available.

**Auto-ignition temperature**

Solid: not applicable  
Gas: not applicable

Decomposition temperature: not determined

**Oxidizing properties**

Not oxidising.

Vapour pressure: not determined  
Vapour pressure: No information available.

Density (at 20 °C): 0,829 g/cm<sup>3</sup> DIN 51757

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

**Solubility in other solvents**

not determined

Partition coefficient: not determined  
Viscosity / dynamic: No information available.  
Viscosity / kinematic: > 20 mm<sup>2</sup>/s  
Flow time: No information available.  
Vapour density: not determined  
Evaporation rate: not determined  
Solvent separation test: No information available.  
Solvent content: No information available.

**9.2. Other information**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**WINKEL WW3000 Haftschmier Spray 500ml**

Revision date: 13.07.2020

Page 7 of 13

Solid content: not determined

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Extremely flammable aerosol.

**10.2. Chemical stability**

The product is stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

**10.5. Incompatible materials**

Oxidizing agents. Pyrophoric or self-heating substances.

**10.6. Hazardous decomposition products**Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.**Further information**

Do not mix with other chemicals.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

No information available.

**Acute toxicity**

Based on available data, the classification criteria are not met.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## WINKEL WW3000 Haftschmier Spray 500ml

Revision date: 13.07.2020

Page 8 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
75-28-5	isobutane				
	inhalation vapour	LC50 1237 mg/l	Mouse.		
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat	Study report (1988)	Group of rats were exposed to test subst
64742-49-0	Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics				
	oral	LD50 5500 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat	Study report (1988)	OECD Guideline 403
106-97-8	butane				
	inhalation (4 h) gas	LC50 658 ppm	Rat	GESTIS	
4259-15-8	zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)				
	oral	LD50 >3100 mg/kg	Rat		
	dermal	LD50 >2000 - <5000 mg/kg	Rabbit		

**Irritation and corrosivity**

Causes skin irritation.

Causes serious eye irritation.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

**STOT-single exposure**

May cause drowsiness or dizziness.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

No information available.

**Additional information on tests**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**SECTION 12: Ecological information****12.1. Toxicity**

Harmful to aquatic life with long lasting effects.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## WINKEL WW3000 Haftschiemier Spray 500ml

Revision date: 13.07.2020

Page 9 of 13

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method	
75-28-5	isobutane						
	Acute fish toxicity	LC50 mg/l	91,42	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
74-98-6	propane						
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane						
	Acute fish toxicity	LC50 mg/l	> 1-10	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Pseudokirchneriella subcapitata	Study report (1995)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 1-10	48 h	Daphnia magna		
	Fish toxicity	NOEC mg/l	2,045	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211
64742-49-0	Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics						
	Acute fish toxicity	LC50 mg/l	>1 - 10	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50	12 mg/l	72 h	Pseudokirchneriella subcapitata	SIDS Initial Assessment Report For SIAM	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	>1 - 10	48 h	Daphnia magna		
	Fish toxicity	NOEC mg/l	1,534	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211
106-97-8	butane						
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## WINKEL WW3000 Haftschiemier Spray 500ml

Revision date: 13.07.2020

Page 10 of 13

	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
4259-15-8	zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)						
	Acute fish toxicity	LC50 mg/l	>2-10	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 mg/l	>240	72 h	Pseudomonas putida		
	Acute crustacea toxicity	EC50 mg/l	>2-10	48 h	Daphnia magna		

**12.2. Persistence and degradability**

The product has not been tested.

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane				
	OECD Guideline 301 F	98%	28		
	Easily biodegradable (concerning to the criteria of the OECD)				

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
74-98-6	propane	1,09
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	3,4 - 5,2
106-97-8	butane	1,09

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The product has not been tested.

**12.6. Other adverse effects**

No information available.

**Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

**List of Wastes Code - residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**List of Wastes Code - used product**



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## WINKEL WW3000 Haftschmier Spray 500ml

Revision date: 13.07.2020

Page 11 of 13

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**SECTION 14: Transport information****Land transport (ADR/RID)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1  
Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0  
Transport category: 2  
Tunnel restriction code: D

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1  
Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0

**Marine transport (IMDG)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Marine pollutant: no  
Special Provisions: 63, 190, 277, 327, 344, 381,959  
Limited quantity: 1000 mL  
Excepted quantity: E0  
EmS: F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1  
Special Provisions: A145 A167 A802

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**WINKEL WW3000 Haftschmier Spray 500ml**

Revision date: 13.07.2020

Page 12 of 13

Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

Warning: Flammable gases.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: isobutane; Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics; butane

Entry 29: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt; 5% n-hexane

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

**Additional information**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Aerosol directive (75/324/EEC)

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 2,3,4,5,6,7,9,10,11,14,15,16.

**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## WINKEL WW3000 Haftschmier Spray 500ml

Revision date: 13.07.2020

Page 13 of 13

ATE: Acute Toxicity Estimate  
STEL (EC) Short Term Exposure Limit  
LC50: Lethal Concentration  
EC50: half maximal Effective Concentration  
ErC50: means EC50 in terms of reduction of growth rate

**Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H229 Pressurised container: May burst if heated.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

**Further Information**

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]:  
Calculation method.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*