



TECHNICAL DATA SHEET

MoS₂ Zahnradspray

Features:

MoS₂ Grease Spray is a bituminous, viscous, solvent-based lubricant. After the solvent has evaporated, a tough, adhering lubricating film remains with a sufficient layer thickness. This lubricating film forms a dry, non-dust-binding, adhesive, pressure- and impact-resistant protective and lubricating film that is tough, elastic and waterproof and does not become brittle in the cold.

- Acts noise-absorbing
- Avoid jerky starting
- Protects against corrosion and wear
- No embrittlement in the cold
- Iso suitable for the preservation of wire ropes
- Tough elastic and waterproof
- Dry lubricating film - does not bind dust

Application Areas:

MoS₂ Grease Spray is used in many areas of industry, e.g. in metallurgical plants and rolling mills, with open gears, for drives in transport and conveyor systems and much more. Due to the good heat resistance, it can also be used in the event of radiant heat or outdoor use (in the heat of the midsummer).

Application:

Remove old lubricant residues with an industrial cleaner, in the case of very heavy soiling with a brush or spatula. Shake the can vigorously until you hear the mixing ball stop. Spray on from a distance of approx. 25 cm. After the solvent has flashed off, a dry lubricating film is created. Depending on the area and location of use, this process should be repeated at self-determined intervals in order to prevent dry running and thus increased wear.

Technical Properties:

Chemical base	bituminous solvent-based lubricant
Color	black
Density	0.96 kg/L
Four-ball test	approx. 2600 N (DIN 51350)

Art. No. **Packaging:**
W 160 104 400 ML