

# 0 6061 9N2 102 - PRO 18V-285

## PRO GDX 18V-285

Bosch Power Tools | © Robert Bosch B.V.

### Technical Specifications

Torque adjustment range, min./max., level 1

**0 / 200 Nm**

Torque adjustment range, min./max., level 2

**0 / 285 Nm**

No-load speed

**0 - 2,800 rpm**

No-load speed (level 1)

**0 - 2,000 rpm**

No-load speed (level 2)

**0 - 2,800 rpm**

Torque settings

**2**

Weight excl. battery

**1.1 kg**

Maximum torque

**285.0 Nm**

Impact rate

**0 - 3,600 bpm**

Impact rate (level 1)

**0 - 3,000 bpm**

Impact rate (level 2)

**0 - 3,600 bpm**

Battery voltage

**18.0 V**

Tool holder

**1/2" square drive with friction ring and through-hole**

**1/4" hex universal holder**

Maximum breakaway torque  
500.0 Nm

Tool dimensions (width)  
73 mm

Tool dimensions (length)  
147 mm

Tool dimensions (height)  
210 mm

Packaging dimensions (width × length × height)  
360 × 444 × 151 mm

Weight incl. battery  
1.70 kg

## Noise Level

The A-weighted noise level of the power tool is typically:

Sound pressure level: 99 dB(A)

Sound power level: 110 dB(A)

Uncertainty: K = 3 dB

