








Instruction Manual

Acid-resistant industrial pressure sprayer

5 Litres



Instructions for use



1. Press the handle down and turn it to the right to fill the tank.
2. Do not exceed the maximum fill level.
3. Close the handle securely and pump 25 times, the maximum recommended number of pumps.
4. Check that all screw mechanisms are firmly tightened so that no air can escape.
5. Open the safety pressure valve when using at 40 PSI.
6. Use the On/Off trigger to regulate the sprayer.
7. Adjust the nozzle at the end for a fine mist or direct spray.
8. Always release the pressure when the job is finished, then empty and rinse the bottle immediately.

Product



General description

- A. Pump handle
- B. Adjustable spray head
- C. Safety valve
- D. Trigger lock
- E. Tank
- F. Pump
- G. Handle grip
- H. Nozzle connection
- I. Acid-resistant gloves

Important

- When using chemicals, always wear protective clothing, gloves and a mask while spraying.
- Avoid spraying during strong gusts of wind.
- If spraying in light wind conditions, always spray with the wind so spray is blown away from you.
- Always release the pressure before filling, maintaining or storing the tank.
- Do not leave the pressure sprayer unattended while it is under pressure.
- The chemical contents are hazardous if swallowed or if they come into contact with the skin. Always consult the chemical supplier's safety instructions or contact a poison control centre or doctor immediately.
- Always review the chemical safety instructions and rinse the tank thoroughly after use.