

## Anti - Seize - Copper



### Features:

- Special high-performance lubricant and very good release agent with antiseize
- effect from a composition of molecular copper particles and a highly
- resistant fully synthetic binder
- High-quality, highly adhesive high-performance lubricant
- High temperature resistant -30 ° C to +1400 ° C, pressure resistant up to 230
- N / mm<sup>2</sup>
- Resistant to water, gasoline, oil, gases etc.
- Can be used as a release agent against corrosion, seizure and wear
- Guarantees the perfect functioning of moving parts even under extreme loads

### Operation Range:

- Excellent use on cable drums, exhaust systems, heating throttle valves,
- brake shafts for disc brakes, brake cams, etc.
- Premium release agent on hot-screw
- Mounting aid for shrink and press-on assemblies, guides, screw connections
- and flanges
- Facilitates tapping
- Protects exposed screw joints and other moving parts or joints

### Technical Data:

Colour: Copper  
 consistency class NLGI: 1  
 Designation: MPF1-30  
 Base oil: PAO  
 Thickener: inorganic  
 Density: 1,1 g/cm<sup>3</sup>  
 Temperature range: -30 - +1400 °C  
 Dropping point: without  
 Article

**Art. No.**  
 W 160 101

**Packaging:**  
 400 ML