

## Commercial Portable / Spot Air-Conditioner

### Key Features

- Effective large space temperature control solution.
- Individual temperature control for large spaces, ideal for consistent cooling.
- LCD screen shows set and ambient temperature, simple to use.
- No external unit required, as compressor is built-in for refrigeration.
- Locking universal wheel for easy mobility.
- Two-speed fan and adjustable nozzles offer customized cooling options.
- Convenient removable built-in water tank.
- Waterproof electrical components for outdoor use.
- No professional maintenance needed with automatic fault diagnosis display feature.



### Special Features

- |  |   |
|--|---|
| • <b>Commercial Marine Grade</b>             | • <b>High Performance GMCC Compressor</b> |
| • <b>LCD Display</b>                         | • <b>Built-in Water Tank</b>              |
| • <b>Adjustable Speed</b>                    | • <b>Adjustable Temperature</b>           |
| • <b>Universal Easy to Move Wheel Design</b> | • <b>Rotary Fully Enclosed Motor</b>      |
| • <b>Hydrophilic Aluminium Fin-stock</b>     | • <b>Evaporator / Compensator</b>         |
| • <b>Inner Thread Copper Tube</b>            | • <b>PET Dust-Proof Filter</b>            |

General features

Model		MAXX – CO-PAC25ZR 220
Cooling capacity	BTU	25000
	Tonnage	2.1 Ton
	HP	3 HP
	Kilowatt	7.3.2 kW
	Square Meter	50 m²
Compressor Type		Rotary Compressor
Air volume		900m³/h
Working Temperature		18-45°C
Refrigerant		R410 / 1300g
Max. Suction Pressure		1.2 MPa
Max. Discharge Pressure		4.5 MPa
Drain tank		Yes
Condensate tank capacity		15 Ltr
LCD screen control & fault detection		Yes
No. of Vents		3
Electrical Details		
Voltage		220-240 V
Frequency		50/60 Hz
Rated Input Power		3000W
Rated Current		13.6 A
Shipping Details		
Unit Dimension		55 x 62 x 116.5 cm
Pack Dimension		59 x 67 x 143 cm
Net Weight		95 kg
Gross Weight		99 kg

BUILT IN WATER TANK  
EASY TO REMOVE AND CLEAN




HIGH-PERFORMANCE  
COMMERCIAL COMPRESSOR



UNIVERSAL WHEELS  
FOR EASY MOVEMENT

HYDROPHILIC ALUMINIUM FIN-STOCK



INNER THREAD  
COPPER TUBE

