

AFi75xx

12"/30 cm

Blower/Exhauster

The compact, air driven AFi75xx ventilator exhausts the air outside of the duct, not in airstream. The hazardous location blower/exhauster provides protection and peace of mind to the user.

Specifications


Model	AFi75xx
Part	AB7000
IMPA Code	591511, 591425
Motor	GAST 4AM-NRV-50C
Motor Type	Totally Encapsulated Air Flame Proof
Operating Temperature	-22°F to +104°F / -30°C, to +40°C
Noise	89 dB @ 1 m
Run Time	Continuous
Weight	38 lbs / 17 kg
Dimensions (h/w/d)	16 x 17 x 16 in / 41 x 43 x 41 cm
Duct Adapters	2
AIR CONSUMPTION AND HORSEPOWER REQUIREMENTS FOR AIR COMPRESSOR*	
Air Pressure (PSIG) Inlet Air	80
Air Consumption	40 scfm / 68 m³/hr
Compressor Hp	6.4 Hp
Induction Ratio	51:1

* Values are shown for single-stage piston-type air compressors operating at 85% efficiency, and working on intake air under standard conditions.

«Certifications & Approvals»

AFi75xx Motor Certification String

Ex II 2 GD c T4+1° C < Ta < +40° C



Performance

Airflow	
Free Air	2,042 cfm (3,471 m³/hr) (measurement @ 80psig inlet air)

Available Accessories

Duct Adapter/Reducer

Order # EC0301

12" (30 cm) - 8" (20cm) diameter Duct Adapter/Reducer for the 30cm AFi75xx



ECKO Flex™ Anti-Static Duct with carrying bag

Order # FDT-1215CBB - 12"(30cm) anti-static duct 15' (4.6 m), w/ carrying bag

Order # FDT-1225CBB - 12"(30cm) anti-static duct 25' (7.6 m), w/ carrying bag

