

RTV Silicone Sealer 70 ml



Application:

The surface on which the silicone is to be used must be clean and free from oil, grease, rust and other agents.

Remove any residue from the old seal before machining.

Applied silicone can be corrected with a spatula.

Use plastic or stainless steel tools.

After cleaning, clean the tools with a paper towel and rinse with a solvent. We recommend using a silicone remover for uncured silicone.

Apply the silicone seal on the surface and wait 10 minutes to assemble the parts together.

Features:

It is a one-component, elastic, acetate-based liquid sealant. The result is a high and durable elastic seal with very good adhesion to the materials used. Resistant to changing weather conditions, UV rays, hot water, oil and grease etc. Resistant to temperatures between -65 ° C and 260 ° C (short term + 300 ° C).

Operation Range:

It is particularly suitable for use in engines, transmissions, components, grease seals, cylinder liners, carburetor covers, water pump.

Technical Data:

Basic	Acetate
Density	approx. 1,10 - 1,25 [g/cm ³]
Strength	approx. 30 [Shore-A]
Skin time	approx. 8 dakika
Curing time	approx. 2mm / gün
Application temperature	+5°C ila +40°C
Temperature resistance	-65 °C to + 260 °C (short term + 300 °C)
Shelf life	+5°C ila +30°C

Art. No.

W 200 501

W 200 502

Packaging:

70 ML

70 ML

Colour:

red

black